(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 18 September 2003 (18.09.2003)

PCT

(10) International Publication Number WO 03/076100 A1

(51) International Patent Classification⁷: C21D 7/02

B21D 11/02,

(21) International Application Number: PCT/SE03/00422

(22) International Filing Date: 13 March 2003 (13.03.2003)

(25) Filing Language:

Swedish

(26) Publication Language:

English

SE

(30) Priority Data:

0200764-9 13 March 2002 (13.03.2002)

- (71) Applicant (for all designated States except US): AVESTAPOLARIT AB [SE/SE]; S-774 80 Avesta (SE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): CARLSSON, Leif [SE/SE]; Bredöl 119, S-465 91 Nossebro (SE). GROTH, Hans [SE/SE]; Gyllenvägen 12, S-774 61 Avesta (SE).
- (74) Agent: BJELKSTAM, Peter; Bergenstråhle & Lindvall AB, P.O. Box 17704, S-118 93 Stockholm (SE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

76100

(54) Title: A METHOD FOR MANUFACTURING AN ULTRA-HIGH-TENSILE, STRETCH FORMED OR STRETCH BENT SHEET METAL PRODUCT OF STEEL

(57) Abstract: A method for manufacturing an ultra-high-tensile sheet method product of steel, at which the initial work piece used is constituted of a metal work piece of iron, alloyed with chromium, nickel and carbon in predetermined proportions. The initial work piece is wholly or partially plastically cold worked by stretch forming or stretch bending at a predetermined temperature and/or deformation degree, that determines and is determining for the yield point of the final product, in providing a strong deformation hardening, that gives the final product a totally or partially many times increased strength or higher yield point, as compared to the yield point of the initial work piece.